

CV 1114

Test Specification No.	Date	To be read in conjunction with K1001, ignoring clauses :- 5.2, 5.8.
D.C.D., W.T. 1147 Issue No.3	18th July 1943.	

<u>TYPE OF VALVE</u> : Transmitting Tetrode		<u>MARKING</u>			
CATHODE : Directly Heated - Thoriated Tungsten		VT114			
ENVELOPE : Metal-Class Construction		10E/168			
COMMERCIAL PROTOTYPE : E.1024.		Serial Number			
<u>RATING</u>		<u>DEGREE OF SECRECY OF VALVE</u>			
Filament Voltage (volts)	10.0	A	NON-SECRET		
Filament Current (amps.)	70.0	A			
Maximum Anode Dissipation (watts)	200	B			
Maximum Operating Frequency (Mc/s)	60				
<u>CAPACITANCES</u> (pF)		<u>DIMENSIONS &amp; CONNECTIONS</u>			
Anode to all other electrodes	20	See Fig. 1			
Grid to all other electrodes	35				
Anode to grid (max.)	2				
<u>NOTES</u>		<u>PACKING</u>			
A:- Cooling of the filament leads and adjacent re-entrant portion of the envelope shall be provided by not less than 10 cu.ft. of air per minute with a pressure drop of the order of 2 inches of water.					
B:- For this dissipation forced air cooling shall be provided by not less than 85 cu.ft. of air per minute with a pressure drop across the valve of the order of 2 inches of water.					

TESTS

To be performed in the order specified, and are additional to those applicable in K1001.

Clause	Test Conditions					Test	Limits		No. Tested
	Vf	Va	Vg2	Vg1	Ia(mA)		Min.	Max.	
	Forced air cooling for the filament leads and the anode shall be provided by not more than 10 cu. ft. and 85 cu. ft. of air per minute, respectively, with a pressure drop across the valve of the order of 2 inches of water.								
a	10.0	Raised slowly to 27.5 kV and maintained till flashing ceases. See Note 1	Strapped		a trace	Hot Flash Process Anode voltage maintained at 27.5 kV for a period of 5 mins. without further flashing. See Note 1.			100%
b	10.0	0	0	0	-	Filament Current (amps.)	66.5	73.5	100%
c	10.0	1 kV	1 kV	-	200	Reverse Control grid current (milliamps)	-	1.0	100%
d	10.0	1 kV	1 kV	-	200	Grid Voltage (volts)	-85	-120	100%
e	10.0	1 kV to 700V.	1 kV to 700V.	-	Maintained at 200	Grid Voltage change (volts)	48	64	100%
f	-	300	300	300	Total cathode current 0.5amp	Filament Voltage (volts)	-	6.0	100%
g	10.0	150	150	150	-	Total Cathode current (amps.)	0.9	1.5	100%
h	10.0	Strapped pulse of peak value 6 kV., half sine wave shape, duration 2 $\mu$ secs. and recurrence frequency 50 c.p.s. to be applied.			-	Emission Current (amps.)	70	-	5% (4)


(Tests continued on page 2).

	Test Conditions				Test	Limits		No. Tested
	V <sub>F</sub>	V <sub>A</sub>	V <sub>G2</sub>	I <sub>A</sub> (mA)		Min.	Max.	
3	See Appendix III of K1001				Capacitances (μF)			25 (1)
					1. Ca - all	16	24	
					2. Cg - all	26.3	43.7	
					3. Cag.	-	2	


k Life - A minimum life of 4000 hours is expected, life failure being considered to occur when the emission of the valve has fallen below 0.5 amp. at V<sub>F</sub> = 6.6 volts, other conditions as in test clause (f).

NOTE 1. Once the conditions specified in test clause (a) have been met, the test conditions need not be repeated for acceptance testing. For this test flash presence there shall be a 300 ohm resistor in series with the applied volts and a capacitance of 0.25 μF in parallel with the supply volts on the supply side of the rectifier.

### OUTLINE DIMENSIONS FIG. 1.



6 No. 4 BAJ 1/2 RD. HD.  
SCREWS EQUALLY  
SPACED ON 140 R.C.D.



ALL DIMENSIONS  
IN MILLIMETRES.