

ELECTRONIC VALVE SPECIFICATIONS

SPECIFICATION AD/CV4083

ISSUE NO. 1, DATED 29TH APRIL 1958

AMENDMENT NO. 1

Page 2 Group D

Inner Amplification Factor

Under "Test Conditions" add the following note:-

" $V_a = V_{g2} = 200V$; $V_{g3} = 0$.

Adjust V_{g1} to give $I_k = 12 \text{ mA}$.

Then apply signal = + 1 volt to $g1$.

Reduce V_{g2} to give $I_k = 12 \text{ mA}$.

Inner amplification factor = Change in V_{g2} .

March 1960
N.16672/D

Admiralty Surface Weapons Establishment

SPECIFICATION AD/CV4083

ISSUE 1 DATED 29th APRIL 1958

AMENDMENT No.2

Page 1. CONNECTIONS

Under Column Heading "Electrode", against "Pin 1",

Amend: "g2" to "g1"

October 1960

Admiralty Surface Weapons Establishment

N.33994/D

ELECTRONIC VALVE SPECIFICATIONS

SPECIFICATION AD/CV.4083 ISSUE 1 DATED 29th APRIL, 1958

AMENDMENT No. 3

(i) Page 2 GROUP D. Inner Amplification Factor

In the column headed "Limits" amend "Min. 34", "Bogey, 42", and "Max. 50", to read "30", "38", and "46" respectively.

(ii) Page 3 GROUP F. TEST POINT (1,000 HOURS)

Heater Current In the column headed "Limits", "Min." and "Max" amend "320" and "380" to read "275" and "325" respectively.

June, 1964.

T.V.C. for A.S.W.E.

VALVE ELECTRONIC

ADMIRALTY SIGNAL AND RADAR ESTABLISHMENT

CV4083

Specification AD/CV4083.

Issue 1 dated 29th April, 1958.

To be read in conjunction with K1001, BS448
and BS1409.SECURITYSpecification

Unclassified

Valve

Unclassified

<u>TYPE OF VALVE</u>	-Reliable Miniature HF Pentode with Flexible leads.		<u>MARKING</u> K1001/4												
<u>CATHODE</u>	-Indirectly heated.		<u>BASE</u> BS448/B7G/F												
<u>ENVELOPE</u>	-Glass		<u>CONNECTIONS</u>												
<u>PROTOTYPE</u>	-CV2209 (but without limiting diode on G3)		<u>Pin</u> <u>Electrode</u>												
<u>R.E.T.M.A. Designation</u>	-		1 g ₂ 2 k 3 h 4 h 5 a 6 g ₃ 7 g ₂												
<u>RATINGS</u> (All limiting values are absolute)		<u>Note</u>	<u>DIMENSIONS</u> See BS448												
Heater Voltage	(V)	6.3	<table border="1"> <thead> <tr> <th>Dimensions(mm)</th> <th>Min.</th> <th>Max.</th> </tr> </thead> <tbody> <tr> <td>A. seated height</td> <td>-</td> <td>47.5</td> </tr> <tr> <td>C. diameter</td> <td>16.0</td> <td>19.0</td> </tr> <tr> <td>D. length of leads</td> <td>38.0</td> <td>-</td> </tr> </tbody> </table>	Dimensions(mm)	Min.	Max.	A. seated height	-	47.5	C. diameter	16.0	19.0	D. length of leads	38.0	-
Dimensions(mm)	Min.	Max.													
A. seated height	-	47.5													
C. diameter	16.0	19.0													
D. length of leads	38.0	-													
Heater Current	(A)	0.3													
Max. Heater-Cathode Voltage	(V)	±150													
Max. Operating Anode Voltage	(V)	300													
Max. Anode Voltage (I _a = 0)	(V)	550													
Max. Operating Screen Voltage	(V)	300													
Max. Screen Voltage (I _{g2} = 0)	(V)	400													
Max. Anode Dissipation	(W)	3.0													
Max. Screen Dissipation	(W)	1.5													
Max. Bulb Temperature	(°C)	200													
Max. Shock (short duration)	(g)	500													
Max. Acceleration (continuous operation)	(g)	2.5													
Inner Amplification Factor (μ _{g1} g ₂)		42													
Mutual Conductance	(mA/V)	4.0													
Anode Impedance	(megohm)	0.1													
<u>CAPACITANCES (pF)</u>			<u>MOUNTING POSITION</u>												
C ₁ in (nom)		7.2	Any												
C ₁ out (nom)		4.5													
C ₁ g ₁ (max)		0.01													

NOTESA. Measured at V_a = V_{g2} = 200V; V_{g1} = -3.45V, V_{g3} = 0; (I_a = 7.5 mA; I_{g2} = 4.5 mA).

B. Measured with close fitting metal screen.

C. Caution to Electronic Equipment Design Engineers: Special attention should be given to the temperature of valves to be operated in aircraft. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for life tests are imposed on the valve and will be reduced appreciably if absolute maximum ratings are exceeded. Both reliability and performance will be jeopardised if heater voltage ratings are exceeded: life and reliability performance are directly related to the extent that the heater voltage is maintained at its rated value.

CV4083

TESTS

Page 2

To be performed in addition to those applicable in K1001.
 Tests shall be performed in the specified order unless otherwise agreed with the Inspecting Authority.

Test Conditions - unless otherwise specified.

V_a (Supply) 200V
 V_{g2} (Supply) 200V
 V_{g3} (Supply) 0V
 V_{g1} (Supply) 0V
 V_h (Supply) 6.3V
 R_k (Ω) 287

K1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units
						Min	LAL	Bogey	UAL	Max	ALD	
7.1	Glass Strain		6.5	1								
	<u>GROUP A</u>											
	Electrode Insulation	$V_h = 6.3V$ Note 1 V_{g1} to all = -100V V_{g2} to all = -300V V_{g3} to all = -300V V_a to all = -300V	100%		R	100	-	-	-	-	-	M Ω
			100%		R	100	-	-	-	-	-	M Ω
			100%		R	100	-	-	-	-	-	M Ω
			100%		R	100	-	-	-	-	-	M Ω
	Reverse Grid Current	$R_{g1} = 500K \Omega$ max.	100%		I_{g1}	-	-	-	-	0.5	-	μA
	<u>GROUP B</u>	<u>Combined AQL</u>	1.0									
	Heater Current		0.65	11	I_h	275	-	300	-	325	-	mA
	hk Leakage Current	$V_{hk} = \pm 100V$ Note 3 $V_{hk} = -100V$ Cathode Positive	0.65	11	I_{hk}	-	-	-	-	20	-	μA
					V2 I_{hk}	-	-	-	5	-	-	μA
	Anode Current		0.65	11	I_a	5.6	-	7.1	-	8.6	-	mA
					V2 I_a	To be recorded and agreed later						mA
	g1 Cut-off volts	$I_a = 0.1$ mA	0.65	11	$-V_{g1}$	-	-	-	-	11	-	V
	g3 Cut-off volts	Note 7.	0.65	11	$-V_{g3}$	5	-	-	-	11.5	-	V
	Mutual Conductance		0.65	11	g_m	3.15	-	4.05	-	5.4	-	mA/V
					V2 g_m	To be recorded and agreed later						mA/V
	Screen Current		0.65	11	I_{g2}	2.7	-	4.35	-	6.0	-	mA
					V2 I_{g2}	To be recorded and agreed later						mA
	<u>GROUP C</u>	<u>Combined AQL</u>	6.5									
	Change of Mutual Conductance	$V_h = 5.7V$ Note 2 $V_h = 6.9V$	2.5	1	Δg_m	-	-	-	-	15	-	%
	Reverse Grid Current		2.5	1	I_{g1}	-	-	-	-	1.0	-	μA
	Current	$V_a(b) = V_{g2}(b) = 300V$; $R_k = 560 \Omega$ $R_{g1} = 500K \Omega$ Note 6.										
11.1	Vibration Noise	$V_a(b) = V_{g2}(b) = 250V$; $V_{g3}(b) = 0$; $V_{g1}(b) = 4.5V$; $R_L = 2K \Omega$ Note 5.	2.5	1	V_{gAC}	-	-	-	-	15	-	mV RMS
5.12	<u>GROUP D</u>		6.5	1A								
5.9	Lead fragility Capacitances	No voltages Measured on 1 Mc/s bridge with valve mounted in a fully shielded socket. Valve screened.	6.5	1C	C_{in}	6.2	-	7.2	-	8.3	-	pF
					C_{out}	3.7	-	4.3	-	5.0	-	pF
					C_{ag1}	-	-	-	-	0.01	-	pF
	Inner Amplification Factor	$I_k = 12$ mA	6.5	1A	$M_{g1,g2}$	34	-	42	-	50	-	

K1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units	
						Min.	LAL	Bogey	UAL	Max.	ALL		
11.2	<u>GROUP E</u>												
	Resonance Search	$V_{a(b)} = V_{g2(b)} = 250V$; RL = $2K \Omega$ Frequency: (1) 25 to 200c/s (2) 200 to 500c/s (3) 500 to 2500c/s Note 8.	2.5	1C	V_{aAC}	-	-	-	-	Record	-	(mV (RMS)	
					V_{aAC}	-	-	-	-	Record	-	(mV (RMS)	
					V_{aAC}	-	-	-	-	Record	-	(mV (RMS)	
	11.3	Fatigue	$V_h = 6.9V$ Note 4.		1A								
		<u>POST FATIGUE TESTS</u>											
		hk Leakage Current	<u>Combined AQL</u> $V_{hk} = \pm 100V$ Note 3.	4	2.5	I_{hk}	-	-	-	-	40	-	μA
		Reverse Grid Current	$R_{g1} = 500K \Omega$ max.	2.5	2.5	I_{g1}	-	-	-	-	1.0	-	μA
		Mutual Conductance		2.5	g_m	2.8	-	-	-	5.4	-	mA/V	
	11.1	Vibration noise	As in Group C	2.5		V_{aAC}	-	-	-	-	25	-	(mV (RMS)
11.4	Shock	Hammer angle= 30° No Voltages	-	1A									
	<u>POST SHOCK TESTS</u>												
	hk Leakage Current	<u>Combined AQL</u> $V_{hk} = \pm 100V$ Note 3	4.0	2.5	I_{hk}	-	-	-	-	40	-	μA	
	Reverse Grid Current	$R_{g1} = 500K \Omega$ max.	2.5	2.5	I_{g1}	-	-	-	-	1.0	-	μA	
	Mutual Conductance		2.5	g_m	2.8	-	-	-	5.4	-	mA/V		
11.1	Vibration noise	As in Group C	2.5		V_{aAC}	-	-	-	-	25	-	(mV (RMS)	
A V1/5	<u>GROUP F</u>												
	Life	$V_h = 6.3V$; $V_{a(b)} = 250V$ $R_k = 150 \Omega$ $R_{g1} = 500K \Omega$		1									
	<u>STABILITY LIFE (1 HOUR)</u>												
	Change in Mutual conductance		1.0	1A	Δg_m	-	-	-	-	10	-	%	
	5.3	Test point (500 hrs) Inoperatives	<u>Combined AQL</u>	6.5	2.5								
		Heater Current		2.5	2.5	I_h	275	-	-	-	325	-	mA
	5.3	hk Leakage Current	$V_{hk} = \pm 100V$ Note 3	2.5	2.5	I_{hk}	-	-	-	-	40	-	μA
		Reverse Grid Current	$R_{g1} = 500K \Omega$ max.	2.5	2.5	I_{g1}	-	-	-	-	1.0	-	μA
		Mutual Conductance		2.5	g_m	2.7	-	-	-	5.4	-	mA/V	
		Average change of Mutual Conductance			Δg_m	-	-	-	-	15	-	%	
	Anode Current		4.0	I_a	5.05	-	-	-	8.6	-	mA		
	Electrode Insulation	$V_h = 6.3V$ Note 1 V_{g1} to all = -100V V_{g2} to all = -300V V_{g3} to all = -300V V_a to all = -300V	4.0	4.0	R	50	-	-	-	-	-	M Ω	
AV1/5.6	<u>TEST POINT (1000 HOURS)</u>												
	<u>Combined AQL</u>		10.0										
	Inoperatives		4.0										
	Heater Current		4.0	4.0	I_h	320	-	-	-	380	-	mA	
	hk Leakage Current	$V_{hk} = \pm 100V$ Note 3	4.0	4.0	I_{hk}	-	-	-	-	40	-	μA	
	Reverse Grid Current	$R_{g1} = 500K \Omega$ max.	4.0	4.0	I_{g1}	-	-	-	-	1.0	-	μA	
	Mutual Conductance		4.0	4.0	g_m	2.5	-	-	-	5.4	-	mA/V	
Anode Current		6.5	6.5	I_a	4.6	-	-	-	8.6	-	mA		

K1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units
						Min	LAL	Bogey	UAL	Max	ALD	
A IX/2.5	<u>GROUP C</u> Electrical Re-test after 28 days holding period.			100%								
A VI/5.6	Inoperatives Reverse Grid Current	$R_{g1} = 500K \text{ max.}$	0.5 0.5		I_{g1}	-	-	-	-	0.75	-	μA

NOTES

1. Heater and Cathode strapped and considered as a single electrode.
2. Change of Mutual Conductance is expressed as a percentage, so:-

$$\frac{(gm \text{ at } 6.3V) - (gm \text{ at } 5.7V)}{(gm \text{ at } 6.3V)} \times 100\%$$

3. Heater positive and negative successively.
4. Valves shall be vibrated in each of the three required planes for not less than 30 hours and not less than 100 hours total. Heater switched 1 minute on, 3 minutes off. No other voltages. Min. peak acceleration = 5g. Frequency = 170 ± 5 c/s.
5. The valves shall be mounted so that the direction of vibration is parallel to the minor axis of the valve electrode structure.

Vibration frequency = any fixed frequency in the range 25 - 100 c/s. Min. peak acceleration = 2g. The test shall be of sufficient duration to obtain a steady reading of noise output.

6. Prior to this test the valve shall be pre-heated for 5 minutes under the test conditions. The maximum time between pre-heating and testing shall be 2 seconds. I_{g1} shall not be rising or out of limit after a total of 10 minutes.
7. $V_a = 200V$; $V_{g2} = 100V$; adjust V_{g1} so that $I_k = 10 \text{ mA}$ when $V_{g3} = 0$. Then adjust V_{g3} to give $I_a = 0.1 \text{ mA}$.
8. At present readings for this test are to be recorded. It is envisaged that a subsequent issue of the specification will include limit figures for this test.

CV4083/1/4

Z.16974.R.