

20A3


THYRATRON GAS TETRODE

Indirectly heated—for use as Gas Relay

<u>RATING</u>			
Heater Voltage (volts)	V_h		6.3
Heater Current (amps)	I_h		0.6
Arc Voltage Drop (volts)			8
Maximum Forward Anode Volts	V_a		650
Maximum Peak Inverse Anode Voltage (volts)	P.I.V.(max)		1300
Maximum Shield Grid Voltage (volts)	$V_{g2}(\text{max})$		-100
Maximum Control Grid Volts	$V_{g1}(\text{max})$		-100
Maximum Peak Cathode Current (mA)	$I_k(\text{pk})\text{max}$		500
Maximum Average Cathode Current (mA)	$I_k(\text{av})\text{max}$		100
Control Grid Circuit Res. (Megohms)	R_{g1}	0.01-10.0	
Control Ratio G1			250 •
Control Ratio G2			1000 †
	• $V_{g2} = 0$	$R_{g1} = 0$	
	† $V_{g1} = 0$	$R_{g1} = 0$	$R_{g2} = 0$
<u>IMPORTANT</u>			
1) Heater to cathode voltage must never exceed 25 volts peak.			
11) The heater must be switched on for 10 sec min before anode voltage is applied.			
111) All maximum ratings are absolute values, not design centres.			
<u>DIMENSIONS</u>			
Overall Length Maximum (mm)			54
Maximum Diameter (mm)			19
Maximum Seated Height (mm)			47.5
Approximate Nett Weight (ozs)			$\frac{1}{2}$
Approximate Packed Weight (ozs)			$\frac{1}{2}$
<u>MOUNTING POSITION</u> - Unrestricted.			

20A3
THYRATRON GAS TETRODE
Indirectly heated—for use as Gas Relay

BASE - Miniature Button 7, pin B7G.



Viewed from free end of pins.

CONNEXIONS

Pin 1	Grid 1	g1
Pin 2	Cathode	k
Pin 3	Heater	h
Pin 4	Heater	h
Pin 5	Grid 2	g2
Pin 6	Anode	a
Pin 7	Grid 2	g2

20A3
THYRATRON GAS TETRODE
 Indirectly heated—for use as Gas Relay

AVERAGE CHARACTERISTIC CURVES: V_a/V_g
 $R_{g1}=0$ $R_{g2}=0$

