



OB2

OB2

VOLTAGE REGULATOR

MINIATURE GLOW-DISCHARGE TYPE

GENERAL DATA

Electrical:

Cathode Cold

Mechanical:

Mounting Position Any

Maximum Overall Length 2-5/8"

Maximum Seated Length 2-3/8"

Length, Base Seat to Bulb Top (Excluding tip) 2" ± 3/32"

Maximum Diameter 3/4"

Weight (Approx.) 0.3 oz

Bulb T-5-1/2

Base Small-Button Miniature 7-Pin (JETEC No. E7-1)


Basing Designation for BOTTOM VIEW 5B0

Pin 1 - Anode

Pin 2 - Cathode

Pin 3 - Internal
Connection—
Do Not Use

Pin 4 - Cathode



Pin 5 - Anode

Pin 6 - Internal
Connection—
Do Not Use

Pin 7 - Cathode

Maximum and Minimum Ratings, Absolute Values:

AVERAGE STARTING CURRENT ♦ 75 max. ma.

DC CATHODE CURRENT { 30 max. ma.
5 min. ma.

FREQUENCY 0 max. cps

AMBIENT-TEMPERATURE RANGE -55 to +90 °C

Circuit Values:

Shunt Capacitor 0.1 max. μf

Series Resistor See note below

CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

	Min.	Ave.	Max.	
DC Anode-Supply Voltage	133■	—	—	volts
Anode Breakdown Voltage	—	115	133*	volts
Anode Voltage Drop	101•	108	114*	volts
Regulation (5 to 30 ma.)	—	1	4*	volts

♦ Averaged over starting period not exceeding 10 seconds. This starting period must be followed by a steady-state operating condition of at least 20 minutes, or tube performance will be impaired.

■ Not less than indicated supply voltage should be provided to insure "starting" throughout tube life.

* Maximum individual tube value during useful life.

• Minimum individual tube value during useful life.

The operating considerations and circuit information shown under Type OA2 also apply to Type OB2

← Indicates a change.