

3EJ7

Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 3EJ7 is the same as the 6EJ7 except for the following items:
Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	3.4	volts

3ER5

High-Mu Triode

7-PIN MINIATURE TYPE

The 3ER5 is the same as the 6ER5 except for the following items:
Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	2.8	volts

3FH5

High-Mu Triode

7-PIN MINIATURE TYPE

The 3FH5 is the same as the 6FH5 except for the following items:
Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	3.0	volts
Warm-up time (Average) : : : : :	11	sec



3FS5

Beam Hexode

7-PIN MINIATURE TYPE

The 3FS5 is the same as the 6FS5 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	2.9	volts
Warm-up time (Average)	11	sec

3GK5

High-Mu Triode

7-PIN MINIATURE TYPE

The 3GK5 is the same as the 6GK5 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	2.8	volts
Warm-up time (Average)	11	sec

