

AMPEREX TUBE TYPE 6759

6759

TENTATIVE DATA

The 6759 is a three electrode, forced air-cooled tube designed with special characteristics as a low impedance, RF industrial oscillator to deliver maximum power under varying load conditions.

The filament is thoriated tungsten. The anode is capable of dissipating 6 KW. Maximum ratings apply up to 30 mc.

The 6759 has a heavy wall, high dissipation and heat storage copper anode and an extremely rigid, coaxial grid structure.

Filament connections are made with heavy, heat dissipating, permanently attached, flexible leads eliminating difficulties due to contact resistance at the terminals.

The tube design also incorporates wide spacings between the elements which, together with the rugged mechanical supports, prevent internal shorting.

GENERAL CHARACTERISTICSELECTRICAL DATA

Filament	Thoriated tungsten
Filament Voltage	12.6 volts
Filament Current	33 amperes
Starting Current (cannot be exceeded even momentarily)	63 amperes
Peak Cathode Current ¹	10 amperes
Amplification Factor ($I_b = 1$ amp., $E_b = 2000$ volts)	9
Transconductance ($I_b = 1$ amp., $E_b = 2000$ volts)	7700 micromhos
Plate Resistance	1180 ohms
Direct Interelectrode Capacitance	
Grid to Plate	15.0 uuf
Grid to Filament	12.0 uuf
Plate to Filament	2.0 uuf

MECHANICAL DATA

Mounting Position	vertical with cooler down
Max. Temperature of Seals	180° C
Net Weight (approx.)	8½ lbs.

COOLING CHARACTERISTICS - Forced Air

Plate Dissipation	3	4.5	6.0 KW
Min. Air Flow	190	250	350 CFM
Min. Static Pressure	1.21	1.50	2.50 inches of water

ACCESSORIES

Air Flow Chamber	Amperex Type #S-3705
External Grid Connector	Amperex Type #S-17288

¹ Represents maximum usable cathode current for any condition of operation.

MAXIMUM RATINGS AND TYPICAL OPERATING CONDITIONSOscillator, Class C - Three Phase, Full-Wave Supply

Maximum Ratings, Absolute Values (per tube)

	CCS
DC Plate Voltage	7000 volts d-c
DC Plate Current	1.9 amperes d-c
DC Grid Voltage	-1550 volts d-c
DC Grid Current (Full Load)	0.090 amperes d-c
DC Grid Current (No Load)	0.135 amperes d-c
Grid Dissipation	55 watts
Plate Input	12 kilowatts
Plate Dissipation	6 kilowatts

Typical Operation (per tube)

	CCS Full Load	CCS No Load
DC Plate Voltage	7000 volts d-c	7000 volts d-c
DC Plate Current	1.72	0.550 amperes d-c
DC Grid Voltage	-820	-1220 volts d-c
RF Grid Voltage	1470	— volts
DC Grid Current	0.082	0.122 amperes d-c
Grid Resistor	10	10 kilohms
Plate Input	12	3.8 kilowatts
Plate Dissipation	3.85	— kilowatts
Plate Power Output	8.15	— kilowatts
Efficiency	68	— per cent
Equipment Power Output (approx.)	6	— kilowatts

Oscillator, Class C - Single Phase, Full Wave Supply

Maximum Ratings, Absolute Values (per tube)

	CCS
DC Plate Voltage	6300 volts d-c
DC Plate Current	1.7 amperes d-c
DC Grid Voltage	-1350 volts d-c
DC Grid Current (Full Load)	0.074 amperes d-c
DC Grid Current (No Load)	0.110 amperes d-c
Grid Dissipation	35 watts
Plate Input	12 kilowatts
Plate Dissipation	6 kilowatts

Typical Operation (per tube)

	CCS Full Load	CCS No Load
DC Plate Voltage	6300 volts d-c	6300 volts d-c
DC Plate Current	1.55	0.490 amperes d-c
DC Grid Voltage	-740	-1100 volts d-c
DC Grid Current	0.074	0.110 amperes d-c
Grid Resistor	10	10 kilohms
Plate Input	12	3.8 kilowatts
Plate Dissipation	3.85	— kilowatts
Plate Power Output	8.15	— kilowatts
Tube Efficiency	68	— per cent
Equipment Power Output (approx.)	6	— kilowatts

No load condition is valid for plate current of 0.300 amperes d-c or less

6759

6759

6759 CONSTANT CURRENT CHARACTERISTIC

