




OUTPUT PENTODE  
 PENTHODE DE SORTIE  
 ENDPENTHOLE

Heating : indirect; parallel supply  
 Chauffage: indirect; alimentation-  
 parallèle  
 Heizung : indirekt; Parallelspeisung

$V_f = 6,3 \text{ V}$   
 $I_f = 0,9 \text{ A}$

Dimensions in mm  
 Dimensions en mm  
 Abmessungen in mm



Base, culot, Sockel: P

Operating characteristics class A  
 Caractéristiques d'utilisation classe A  
 Betriebsdaten Klasse A

$V_a$	=	250 V
$V_{g2}$	=	250 V
$R_k$	=	150 $\Omega$
$V_{g1}$	=	-6 V
$I_a$	=	36 mA
$I_{g2}$	=	4 mA
S	=	9 mA/V
$R_1$	=	50 k $\Omega$
$R_a$	=	7 k $\Omega$
$W_o$ ( $d_{tot} = 10\%$ )	=	4,5 W
$V_1$ ( $d_{tot} = 10\%$ )	=	4,2 $V_{eff}$
$V_1$ ( $W_o = 50 \text{ mW}$ )	=	0,35 $V_{eff}$
$\mu_{g2g1}$	=	23

Operating characteristics class AB  
 Caractéristiques d'utilisation classe AB  
 Betriebsdaten Klasse AB

$V_a$	=	250	V	
$V_{g2}$	=	250	V	
$R_k$	=	140	$\Omega$	
$R_{aa}$	=	10	k $\Omega$	
$V_i$	=	0	$V_{eff}$	
$I_a$	=	2x24	2x28,5	mA
$I_{g2}$	=	2x2,8	2x4,6	mA
$W_o$	=	0	8,2	W
$d_{tot}$	=	0	3,1	%

Limiting values  
 Caractéristiques limites  
 Grenzdaten

$V_{ao}$	= max.	550 V
$V_a$	= max.	250 V
$W_a$	= max.	9 W
$V_{g2o}$	= max.	550 V
$V_{g2}$	= max.	275 V
$W_{g2} (V_i = 0)$	= max.	1,2 W
$W_{g2} (W_o = \max)$	= max.	2,5 W
$I_k$	= max.	55 mA
$V_{g1} (I_{g1} = +0,3 \mu A)$	= max.	-1,3 V
$R_{g1}$	= max.	1 M $\Omega$
$V_{kf}$	= max.	100 V
$R_{kf}$	= max.	5 k $\Omega$

Remark, Observation, Bemerkung

The tube should only be used with automatic or semi-automatic bias

Le tube ne sera utilisé qu'avec polarisation automatique ou semi-automatique

Die Röhre soll nur mit automatischer oder mit halb-automatischer Gittervorspannung verwendet werden

**PHILIPS**



*Electronic  
Tube*

**HANDBOOK**

<b>page</b>	<b>EL3N sheet</b>	<b>date</b>
1	1	1953.08.08
2	2	1953.08.08
3	FP	1999.07.04