

2CN3A

Half-Wave Vacuum Rectifier

4-Second Heater Warm-up Time

The 2CN3A is the same as the 3CN3A except for:

Heater Characteristics and Ratings:

Current	0.900 ± 0.050	A
Voltage (ac or dc) at 0.900 A	1.80	V

2CW4

High-Mu Triode

Nuvistor Type

The 2CW4 is the same as the 6CW4 except for:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A	2.1	V
Warm-up Time (Average)	8	s

2CY5

Sharp-Cutoff Tetrode

The 2CY5 is the same as the 6CY5 except for:

Heater Characteristics and Ratings:

Current	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600 A	2.4	V
Warm-up Time (Average)	11	s

2DS4

High-Mu Triode

Nuvistor Type
Having Extended Cutoff Characteristic

The 2DS4 is the same as the 6DS4 except for:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A	2.1	V
Warm-up Time (Average)	8	s

2DV4

Medium-Mu Triode

Nuvistor Type

The 2DV4 is the same as the 6DV4 except for:

Heater a Heater Characteristics and Ratings:

Current	0.450 + 0.030	A
Voltage (ac or dc) at 0.450 A	2.1	V
Warm-up Time (Average)	8	s