



6AF3

# 6AF3

## HALF-WAVE VACUUM RECTIFIER

9-PIN MINIATURE TYPE

For television damper service

### GENERAL DATA

#### Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	6.3 ± 10%	volts
Current . . . . .	1.2	amp

Direct Interelectrode Capacitances (Approx.):<sup>o</sup>

Plate to cathode and heater . . . . .	6	μμf
Cathode to plate and heater . . . . .	9	μμf
Heater to cathode . . . . .	2.8	μμf

#### Mechanical:

Operating Position . . . . .	Any
Maximum Overall Length . . . . .	3-9/32"
Maximum Seated Length . . . . .	2-7/8" ± 1/8"
Diameter . . . . .	0.750" to 0.875"
Dimensional Outline . . . . .	See General Section
Bulb . . . . .	T6-1/2
Cap . . . . .	Skirted Miniature (JEDEC No. C1-2)
Base . . . . .	Small-Button Noval 9-Pin (JEDEC No. E9-1)
Basing Designation for BOTTOM VIEW . . . . .	.9CB

- Pin 1 - Internal Connection—Do Not Use<sup>◆</sup>
- Pin 2 - Same as Pin 1
- Pin 3 - Same as Pin 1
- Pin 4 - Heater



- Pin 5 - Heater
- Pin 6 - Same as Pin 1
- Pin 7 - Same as Pin 1
- Pin 8 - Same as Pin 1
- Pin 9 - Plate
- Cap - Cathode

### DAMPER SERVICE

#### Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system<sup>o</sup>

PEAK INVERSE PLATE VOLTAGE . . . . .	4500 <sup>■</sup> max.	volts
PEAK PLATE CURRENT . . . . .	750 max.	ma
DC PLATE CURRENT . . . . .	185 max.	ma
PLATE DISSIPATION . . . . .	6 max.	watts
PEAK HEATER CATHODE VOLTAGE:		
Heater negative with respect to cathode . . . . .	4500 <sup>*</sup> max.	volts
Heater positive with respect to cathode . . . . .	300 <sup>▲</sup> max.	volts
BULB TEMPERATURE (At hottest point on bulb surface) . . . . .	210 max.	°C

#### Characteristics:

Tube-Voltage Drop for plate ma. = 340 . . . 30 volts

<sup>o</sup> Without external shield.

<sup>◆</sup> Socket terminals 1,2,3,6,7, and 8 should not be used as tie points.

<sup>□</sup> As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

6AF3



6AF3

## HALF-WAVE VACUUM RECTIFIER

- This rating is applicable where the duty cycle of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.
- ▲ The dc component must not exceed 1000 volts.
- ▲ The dc component must not exceed 100 volts.