


### TWIN TRIODE POWER AMPLIFIER OSCILLATOR

The RK-34 is a heater type twin triode power amplifier tube having an isolantite base. It is designed for use as a power amplifier, oscillator or frequency multiplier.



BOTTOM VIEW OF SOCKET

#### HEATER RATING

Heater Voltage	6.3	volts
Heater Current	0.8	amp

#### DIRECT INTERELECTRODE CAPACITANCES—EACH TRIODE

Grid to Plate	2.7	$\mu\text{mf}$
Input	4.2	$\mu\text{mf}$
Output	0.8	$\mu\text{mf}$

#### R-F POWER AMPLIFIER OR OSCILLATOR—PUSH-PULL—CLASS C

##### MAXIMUM RATINGS

D-C Plate Voltage	300	volts
D-C Plate Current (both triodes)	80	ma
Plate Dissipation (both triodes)	10	watts
(Averaged over 1 cycle)		

##### TYPICAL OPERATION

D-C Plate Voltage	300	volts
D-C Grid Voltage	-36	volts
D-C Plate Current	80	ma
D-C Grid Current	20	ma
Peak R-F Input Voltage (grid to grid)	196	volts
R-F Driving Power	1.8	watts
Power Output	16	watts

#### A-F POWER AMPLIFIER—CLASS B

##### MAXIMUM RATINGS

D-C Plate Voltage	300	volts
Peak Plate Current (both triodes)	125	ma
Plate Dissipation (both triodes)	10	watts
(Averaged over 1 cycle)		

##### TYPICAL OPERATION

D-C Plate Voltage	180	300	volts
D-C Grid Voltage	-6	-15	volts
D-C Plate Current (no signal)	30	30	ma
D-C Plate Current (max. signal)	70	70	ma
D-C Grid Current (max. signal)	16	12	ma
Peak A-F Input Voltage (grid to grid)	100	100	volts
A-F Driving Power	0.7	0.5	watts
Load Resistance (plate to plate)	6000	10000	ohms
Power Output	7.8	13	watts

#### A-F POWER AMPLIFIER—CLASS A

##### (Two Triodes Connected in Parallel)

##### MAXIMUM RATINGS

D-C Plate Voltage	300	volts
Plate Dissipation	10	watts

##### TYPICAL OPERATION

D-C Plate Voltage	300	volts
D-C Grid Voltage	-16	volts
D-C Plate Current	25	ma
Amplification Factor	13	
Plate Resistance	2950	ohms
Transconductance	4400	$\mu\text{mhos}$
Load Resistance	5000	ohms
Power Output	0.8	watts

#### OPERATING NOTES

##### FREQUENCY RANGE

The RK-34 may be operated at the maximum ratings at frequencies up to 240 megacycles. Above 240 megacycles the reduced efficiency realized requires that the plate voltage be lowered to prevent the plate dissipation from exceeding the maximum rated value.

##### BIAS

At least 15 volts of fixed bias should be used with 300 volts on the plate to protect the tube in case of failure of the bias or excitation.

##### PLATE TEMPERATURE

The plates of the RK-34 will not show color when operated at the maximum rated plate dissipation. Dissipations above the rated value should be avoided.

